

36370

CHRYSLER SEBRING TOURING CONVERTIBLE 2.7L V6 SINGLE EXHAUST

7/23/2014

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 3500 LBS. TRAILER WEIGHT & 350 LBS. TONGUE WEIGHT.

DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY.

WARNING: ALL NON-TRAILER LOADS APPLIED TO THIS PRODUCT MUST BE SUPPORTED BY 18050 STABILIZING STRAPS.

** FAILURE TO PROPERLY SUPPORT NON-TRAILER LOADS WILL VOID PRODUCT WARRANTY**

HAVING INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 1-800-798-0813

HAVING INSTALLATION QUESTIONS: CALL TECHNICAL SOFTORT AT 1-000-770-0015				
Parts List				
ITEM QTY PART NUMBER DESCRIPTION				
1 1 1/2" FISHWIRE TOOL			PASSENGER SIDE FRAME RAIL	
2	4	1_2 - 13 x 4	HEX BOLT	EXISTING HOLE -
3	1	CM-SP6	.250 x 1.00 x 3.00" SQUARE HOLE SPACER	USE TO FISHWIRE
4	1	1/2-13 x 1 1/2	CARRIAGE BOLT	ENLARGE THIS HOLE
5	5	HFN 1213	HEX FLANGE NUT	
6	7	FW12	FW, 12, ZP	
INS F INS	TALL PROFIOVION	VEIGHT: 27 LBS .TIME ESSIONAL: 30 MIN .DE (DIY): 60 MIN .NOTES:	MINUTES	AIL EXISTING HOLE(4) DESIGNED FOR USE WITH BALL MOUNT # 36063B

INSTALLATION STEPS

- 1) Raise hitch into position between frame rails as shown. Push exhaust to side or lower if needed.
- 2) Install the four 4" hex bolts with washers from the outside of frames as shown (use washers on forward most holes as shown). Fasten with nuts finger tight to the sideplates.
- 3) With hitch in position, enlarge hole in frame at the flange of the passenger side plate with a 17/32" drill bit to fit a 1/2" bolt.
- 4) Fishwire 1 1/2" carriage bolt with square hole spacer through existing square hole in frame to the enlarged hole and fasten to side plate with nut. Finger tight only.
- 5) With all fasteners in place, torque all 1/2" hardware to 110 ft.-lb.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

CURT Manufacturing LLC., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, CURT Manufacturing LLC., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. CURT Manufacturing LLC.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.