

CATALOG NUMBER.....217313
 APPLICATIONMazda 323 3 dr Hatchback,
 Except 4 W. D. & 86 LX model
 HITCH CAPACITY1000 pounds gross trailer weight 100 pounds maximum tongue load
 OR the maximum load specified by the vehicle manufacturer;
 WHICHEVER IS LESS.

PLEASE NOTE: This product complies with safety specifications and requirements for connecting devices and towing systems of the state of New York and regulation V.E.S.C. V-5.

1. Remove materials and lift any floor covering in car's trunk. Place the hitch on car centered and square so hitch chassis bracket fits on 1 x 1" boxed section under trunk floor and hitch bumper bracket locates on steel part of rear bumper under the fascia. See diagram.
2. Using the hitch as a template mark steel bumper and boxed section under trunk floor for hitch bracket holes. Centerpunch and drill through two thicknesses for 3/8" diameter mounting screws on both bumper and boxed floor section.
3. Temporarily remove the rear bumper. Bumper unbolts inside the trunk at the rear body panel, and at rear of wheel openings on both sides of car.
4. Mount hitch to the rear bumper using fasteners ② as shown in diagram. Access for washers and nuts is made through holes in forward surface of bumper. Final tighten fasteners ② until snug, do not crush box section.
5. Carefully reinstall rear bumper with hitch. Mount hitch to trunk floor using fasteners ① as shown with large fender washers inside trunk area. Final tighten fasteners ① until snug, do not crush box section.
6. Recheck all fasteners occasionally for tightness.

FASTENERS:

- ① (2) 3/8 x 2" screw
 (2) 3/8" fender washer
 (2) 3/8" flat washer
 (2) 3/8" lock nut
- ② (2) 3/8 x 2 1/2" screw
 (2) 3/8" flat washer
 (2) 3/8" lock nut

