

TRAILER HITCH MOUNTING INSTRUCTIONS

CATALOG NUMBER257210
APPLICATIONLexus Coupe SC 300 & 400,
HITCH CAPACITY2500 pounds gross trailer weight 200 pounds maximum tongue load
OR the maximum load specified by the vehicle manufacturer;
WHICHEVER IS LESS.

- PLEASE NOTE:
- A. This hitch features a removable ball mount. This hitch is not intended for use as a weight distributing hitch. Before towing, the hitch pin and retainer clip MUST be in place securing ball mount to receiver.
 - B. This product complies with safety specifications and requirements for connecting devices and towing systems of the state of New York and regulation V.E.S.C. V-5.
1. Under the rear of car locate the exhaust mufflers left and right side of car. Mufflers are supported at the rear by a flexible support and bracket bolted into chassis left and right sides. Large "tie down" plates are bolted under exhaust support brackets using four 12mm screws each.
 2. Remove four 12mm screws each bracket and return "tie-down" brackets to car's owner for re-installation should hitch be removed..
 3. This hitch will bolt in place where "tie-down" brackets were removed. Use same 12 x 40mm fasteners removed to install hitch. Refasten exhaust support brackets at two forward screws at bottom of hitch plates.
 4. Final tighten fasteners as specified on reverse of these instructions. Recheck all fasteners occasionally for tightness.